

A new breed of Schrödinger's cats: super-polynomial complex states

Huy Nguyễn Lê,¹ Yu Cai,¹ Xingyao Wu,¹ and Valerio Scarani^{1,2}

¹Centre for Quantum Technologies, National University of Singapore, 3 Science Drive 2, 117543, Singapore

²Department of Physics, National University of Singapore, 2 Science Drive 3, 117542, Singapore

Complexity is often invoked alongside with size and mass as a characteristic of macroscopic quantum objects, but its characterization has been rather elusive. Here we present an explicit construction of multiqubit states, whose complexity grows super-polynomially in the number of qubits, and discuss their properties. Such a state can be a new candidate for the Schrödinger's cat, paving the way to probing quantum mechanics in the region of high complexity. The measure used to quantify complexity is the tree size of a quantum state, which is in principle computable and is closely related to the size of a multi-linear formula.

Introduction. – Quantum mechanics is one of the most tested theories, and it has been verified on different kinds of physical systems. However, when quantum formalism is applied to objects observed in our daily life, something seemingly absurd occurs. The Schrödinger's cat presents such a paradox, where an object is placed in a superposition of two macroscopically distinct states, “dead” and “alive.” Various coherent superpositions claimed to be the “cat state” were implemented in different physical systems such as mechanical resonators [1, 2], superconducting qubit [3] and heavy molecules [4, 5]. A number of different measures of effective size are proposed to quantify the macroscopicity of these quantum superpositions [6–11]. However, is “size” a good measure that characterizes a classical object such as the Schrödinger cat? The GHZ state, which maximizes most of the size criteria proposed, is simple in the sense that only a small amount of information is required to describe it. Could complexity be a more suitable criterion for a “Schrödinger's cat”? Indeed, one often finds it stated that complexity is likely to play just as important a role as number and size in the boundary between classical and quantum worlds.

Complexity may also be relevant in the context of quantum computing. It is well known that simple quantum states such as matrix product states with bounded bond dimension can be simulated efficiently with classical computers [12–14]. Any state that offers an advantage over classical computing must be significantly complex. We will make it clear below what is meant by “simple” and “complex” in the language of complexity measures. It is natural to ask whether there is any connection between complexity and the power of quantum computing.

As a starting point, we search for complex quantum states. It is often argued that a state randomly selected from the Hilbert space is complex in various senses with high probability [15]. However, to the best of our knowledge there is no explicit example of such states. In this paper, we study an explicit class of states whose complexity grows super-polynomially in the number of qubits. Among the several complexity measures proposed [16–21], we focus on the *tree size* of a quantum state, introduced by Aaronson in an attempt to give a more rigorous foundation to the debate on the possibility of large-scale quantum computing versus a hypothetical breakdown of

quantum mechanics [16]. This measure of complexity is motivated by the work of Raz, who showed that any multi-linear formula for the determinant and permanent of a matrix must be super-polynomial in size [22].

Tree size of a n -qubit state. – Let us first briefly describe the tree size (TS) of a quantum state and the size of a multi-linear formula (MFS). An arbitrary pure quantum state of qubits can be represented by a rooted tree [see Fig. (1)]. Each leaf vertex is labelled with $\alpha|0\rangle + \beta|1\rangle$ for each qubit where α, β are complex coefficients; each non-leaf vertex is labelled with either a $+$ gate or a $\otimes$ gate; and complex multiplicative constants are put at the edges of the $+$ gates [16]. The rooted trees for the Bell state and the 3-qubit GHZ state are given in Fig. (1). The *size* of a rooted tree is defined as the number of leaf vertices. It is obvious that any quantum state can be represented by different rooted trees each with a different size. For example, the state $(|00\rangle + |01\rangle + |10\rangle + |11\rangle)/2$ whose size is 8 can also be written as $|+\rangle|+\rangle$ with size 2. The tree size of a quantum state is taken as the *minimum size over all possible representations*.

For a quantum state $|\Psi\rangle$, the minimal representation with size $\text{TS}(|\Psi\rangle)$ is the most compact way of writing




FIG. 1. Rooted trees of (a) the Bell state and (b) the 3-qubit GHZ state; and (c) a binary tree of the associated multi-linear formula that computes the coefficients of the Bell state.

down that state. This explains why the tree-size is a good measure of complexity: When the most compact form of an object is very complex, it is reasonable to say that the object itself has a high degree of complexity. As an example we consider some of the most commonly encountered n -qubit quantum states. It is not difficult to show that the tree size is $O(n)$ for the GHZ state, $O(n^2)$ for the W state and $O(n^4)$ for the one dimensional cluster state [16]. The tree size of the 2D cluster state is conjectured to be super-polynomial but no proof has yet been given [16].

We observe that quantum states with polynomial tree size are too simple to be useful for measurement-based quantum computation (MBQC). If a quantum state has a polynomial tree-size, its minimal rooted tree can be produced with polynomial computational effort in a classical computer. Moreover, local measurements do not lead to an increase in the tree size of the quantum state [23]. Therefore, MBQC on a polynomial-tree-size quantum state can be simulated in a classical computer with polynomial overhead and hence offers no significant advantage. This supports the conjecture that the 2D cluster state possesses a super-polynomial tree size.

An arbitrary n -qubit quantum state can be written as a superposition of the computational basis states

$$|\Psi\rangle = \sum_{x=0}^{2^n-1} \alpha_x |x\rangle, \quad (1)$$

where each of the terms $|x\rangle$ is a n -bit string $|x_1, x_2, \dots, x_n\rangle$ with $x_i = 0$ or 1 . Therefore, its TS is upper bounded by $n2^n$ [16], but in fact we can do better and show that the tree size of a n -qubit state can not exceed $3 \times 2^{n-1} - 2$. By collecting all the terms $|x\rangle$ with $x_1 = 0$ to one group and those with $x_1 = 1$ to another group one may write the n -qubit state in Eq. (1) as

$$|\Psi\rangle = |0\rangle |\chi_0\rangle + |1\rangle |\chi_1\rangle, \quad (2)$$

where $|\chi_0\rangle$ and $|\chi_1\rangle$ are some quantum states of $n-1$ qubits. Let B_n denote the size of a n -qubit quantum state when written in the form of the above equation, we have $B_n = 2(B_{n-1} + 1)$. Solving this recursive formula with $B_1 = 1$ yields the expected upper bound $B_n = 3 \times 2^{n-1} - 2$. It may be possible to reduce this bound further using an optimized decomposition [25]. Proving the lower bound for the tree size of a quantum state is more difficult and is based on the relation with multi-linear formulas.

Link between quantum states and multi-linear formulas. – As mentioned earlier, the tree-size complexity measure for quantum states is closely related to the size of multi-linear formulas. A multi-linear formula of the complex variables $\{x_1, x_2, \dots, x_n\}$ can be represented by a binary tree with each leaf vertex labelled with a variable x_k or a complex constant [22]. The non-leaf vertices are labelled with either $+$ or $\times$. The size of each binary tree is the number of leaf vertices. The size of a multi-linear formula is the minimum size taken over all possible binary-tree representations.

Now we define an associated multi-linear formula $f_\psi(x_1, x_2, \dots, x_n)$ that maps each bit string $x = \{x_1, x_2, \dots, x_n\}$ to the coefficient α_x , that is,

$$f_\psi(x) = \alpha_x. \quad (3)$$

A binary tree for f_ψ can be obtained from a rooted-tree of the corresponding state $|\Psi\rangle$ by a straightforward procedure: from the rooted-tree of the quantum state, one replaces each $|0\rangle_i$ by $1 - x_i$, $|1\rangle_i$ by x_i , the $\otimes$ gates by a set of binary $\times$ gates [16]. It can be verified that the resulting multi-linear formula indeed computes the coefficients α_x of the state $|\Psi\rangle$. The example for the Bell state is shown in Fig. (1c). It is therefore clear that, from the minimal tree of state $|\Psi\rangle$, one can immediately obtain a multi-linear formula that computes its coefficients (even though there may exist such a formula with smaller size [24]). This implies that $\text{MFS}(f_\psi) = O[\text{TS}(|\Psi\rangle)]$: in other words, *if $f(x)$ has a super-polynomial MFS, then the state $\sum_x f(x) |x\rangle$ has a super-polynomial tree-size* [16].

The determinant and the permanent states. – It is shown in Ref. [22] that any multi-linear formula for the determinant and a permanent of a $m \times m$ matrix must be super-polynomial in size [26]. More specifically, the MFS for both the determinant and permanent is proved to be $m^{\Omega(\log m)}$. This allows us to construct a class of super-polynomial complex quantum states when the number of qubit is a square number, that is, $n = m^2$ with m a positive integer.

For the construction, the qubits are first labelled as $x_{11}, x_{12}, \dots, x_{mm}$ and arranged to a matrix

$$\{x\} = \begin{pmatrix} x_{11} & x_{12} & \cdots & x_{1m} \\ x_{21} & x_{22} & \cdots & x_{2m} \\ \vdots & \vdots & \ddots & \vdots \\ x_{m1} & x_{m2} & \cdots & x_{mm} \end{pmatrix}. \quad (4)$$

So, each bit-string $|x\rangle$ in the expansion of Eq. (1) is associated with a $(0,1)$ matrix $\{x\}$ whose elements are 0 or 1. We call the state $\sum_x \alpha_x |x\rangle$ the determinant (permanent) state if the coefficient α_x is taken as the determinant (permanent) of the corresponding $(0,1)$ matrix. Let $|\det_m\rangle$ and $|\text{per}_m\rangle$ denotes the m^2 -qubit determinant and permanent state, respectively, we have

$$\begin{aligned} |\det_m\rangle &= \sum_{x=0}^{2^n-1} \det(\{x\}) |x\rangle, \\ |\text{per}_m\rangle &= \sum_{x=0}^{2^n-1} \text{perm}(\{x\}) |x\rangle, \end{aligned} \quad (5)$$

where the normalization constants are neglected. The determinant states for $m = 1, 2$ are

$$\begin{aligned} |\det_1\rangle &= |1\rangle, \\ |\det_2\rangle &= -|0110\rangle - |0111\rangle + |1001\rangle \\ &\quad + |1101\rangle + |1101\rangle - |1110\rangle. \end{aligned} \quad (6)$$

As a consequence of the theorem $\text{MFS}(f_\psi) = O[\text{TS}(|\Psi\rangle)]$, the tree size of $|\det_m\rangle$ and $|\text{per}_m\rangle$ must scale as $m^{\Omega(\log m)} = n^{(1/4)\Omega(\log n)}$, which is super-polynomial in n . Since the structure of the permanent and determinant states are very similar, from now on we concentrate on the determinant state and briefly mention the results obtained for the permanent state.

The size of the representation of $|\det_m\rangle$ given in Eq. (5) is enormous for large m . There are 2^{m^2} different $(0,1)$ $m \times m$ matrices. At first sight it may seem that the determinant of $(0,1)$ matrices must be small, yet the largest possible determinant is $2^{-m} \sqrt{(m+1)^{m+1}}$ with equality if and only if there is a Hadamard matrix of order $m+1$ [27, 28]. The Hadamard conjecture states that this is true for $m \equiv 3 \pmod{4}$ but the search for a proof remains a long-standing unsolved problem in mathematics [29]. Moreover, the number of terms left in the expansions of Eq. (5) is equal to the number of $m \times m$ $(0,1)$ matrices with non-vanishing determinant, which is also unknown for large m [30]. For $m \leq 8$ numerical computation shows that this number is larger than $0.3 \times 2^{m^2}$ and hence it grows rapidly with increasing m [28].

A much more compact representation is obtained by using the determinant expansion by minors (Laplace expansion) [31]

$$\det \{x\} = \sum_{j=1}^m (-1)^{i+j} x_{ij} M_{ij}, \quad (7)$$

where M_{ij} is the determinant of $\{x\}$ with row i and column j crossed out. Inserting this expression for the determinant into Eq. (5) and summing over all possible values of x yields the recursive formula

$$|\det_m\rangle = \sum_{j=1}^m (-1)^{i+j} |1\rangle_{ij} |\det_{m-1}\rangle_{ij} |+\rangle^{\otimes (2m-2)}, \quad (8)$$

which is understood as follows: The qubit at row i and column j is in the $|1\rangle$ state, the qubits in the $(m-1) \times (m-1)$ block obtained by removing row i and column j is in the $|\det_{m-1}\rangle$ state, and the remaining $2m-2$ qubits are in the $|+\rangle$ states. Starting from $|\det_1\rangle = |1\rangle$, one may use the recursive formula to generate determinant states with larger numbers of qubits, for instance,

$$|\det_2\rangle = |1\rangle |+\rangle |+\rangle |1\rangle - |+\rangle |1\rangle |1\rangle |+\rangle. \quad (9)$$

The permanent state also adopts the recursive formula in Eq. (8) with all the -1 signs switched to $+1$.

How compact is this new expression? Let us denote by S_m the size of $|\det_m\rangle$ when written as in Eq. (8). By counting the number of leaves we see that

$$S_m = m(S_{m-1} + 2m - 1), \quad (10)$$

from which we obtain $S_m = m! \lambda_m$ with $\lambda_m = \sum_{k=1}^m \frac{2k-1}{(k-1)!}$ which converges rapidly to $3e$. Thus, the tree size of $|\det_m\rangle$ is

$$\text{TS}(|\det_m\rangle) = O(m!). \quad (11)$$

This is the smallest upper-bound we were able to find, which suggests the possibility that the lower-bound $m^{\Omega(\log m)}$ can be improved further.

A less compact but more useful expression for studying the entanglement properties of the determinant state is based on the Leibnitz formula [31]

$$\det \{x\} = \sum_{\sigma} \text{sgn}(\sigma) \prod_{i=1}^m x_{i\sigma_i}, \quad (12)$$

where the summation is taken over all $m!$ possible permutation σ of the set $\{1, 2, \dots, m\}$; the sign is -1 for odd and $+1$ for even permutations. With the help of this formula Eq. (5) can be rewritten as

$$|\det_m\rangle = \sum_{\sigma} \text{sgn}(\sigma) \left(\bigotimes_{i=1}^m |1\rangle_{i\sigma_i} \right) |+\rangle^{\otimes (m^2-m)}. \quad (13)$$

Again, the permanent state has a similar representation with the only difference being the omission of the $\text{sgn}(\sigma)$ terms.

The above formula expresses the determinant state as a sum of $m!$ product states. It is also a minimal product-state expansion [32]. The reason is that any two terms in this expansion have at least a pair of qubits that is in the state $|1\rangle |+\rangle$ in one term and $|+\rangle |1\rangle$ in the other; and any combination of $|1\rangle |+\rangle$ and $|+\rangle |1\rangle$ is a mixed state with respect to either qubit in the pair. Thus, it is not possible to have a product-state expansion that has less than $m!$ terms [33]. As a result, the Schmidt measure of the determinant state is $\log_2(m!)$. This measure is a useful tool for quantifying multi-party entanglement of quantum states [34]. We see that if the Schmidt measure of a n -qubit quantum state is E_S , then the minimal product-state expansion has 2^{E_S} terms and hence the tree size of this state is bounded above by $n2^{E_S}$. As a consequence, a very complex quantum state (with large tree size) must also be highly entangled. The Schmidt measure is also a lower bound of the entanglement persistency which is defined as the smallest number of local measurements needed to disentangle a quantum state with certainty [32, 33]. An examination of local measurements with the help of the recursive formula in Eq. (8) strongly suggests that the entanglement persistency of the determinant state is $n-1$ which is the maximal value achievable for a n -qubit quantum state.

The determinant and permanent states are highly symmetric. The determinant of a matrix changes only its sign under the interchange of any two rows or any two columns while the permanent remains unchanged. If one defines $R_{ij}(C_{ij})$, $i \neq j$, as the unitary operation that swaps the quantum state of the m qubits in row (column) i with that of the m qubits in row (column) j , it can be verified that

$$\begin{aligned} R_{ij} |\det_m\rangle &= C_{ij} |\det_m\rangle = -|\det_m\rangle, \\ R_{ij} |\text{per}_m\rangle &= C_{ij} |\text{per}_m\rangle = |\text{per}_m\rangle, \end{aligned} \quad (14)$$

so the determinant (permanent) state is the eigenvector with eigenvalue -1 (1) of the operators R_{ij} and C_{ij} . One may also check that both the determinant and permanent state are invariant under the matrix transposition operation.

A quantum circuit generating complex states. – Any state with a product-state expansion like that in Eq. (13) can be realized with the help of ancilla qubits [17]. Let s be the smallest integer such that $2^s \geq m!$. We first prepare s ancilla qubits in the equal superposition $|+\rangle_a^{\otimes s}$ and m^2 main qubits in the initial product state $|\Phi_0\rangle = |0\rangle^{\otimes m^2}$. The total state is $\sum_{i=1}^N |i\rangle_a |\Phi_0\rangle$ where $N = 2^s$. Multi-controlled Hadamard and Pauli gates are then used to create the state

$$\sum_{i=1}^{m!} |i\rangle_a |\Phi_i\rangle + \sum_{i=m!+1}^N |i\rangle_a |\Phi_0\rangle, \quad (15)$$

where $|\Phi_i\rangle$ is one of the product state in the expansion of Eq. (13). Note that for the last $N - m!$ states $|i\rangle_a$ of the ancilla qubits, we do nothing to the main qubits. Next, the ancilla qubits are measured in the $\{+, -\}$ basis. For any outcome one may verify that the resulting state is

$$|\Psi_m\rangle = \sum_{i=1}^{m!} c(i) |\Phi_i\rangle + \left(\sum_{i=m!+1}^N c(i) \right) |\Phi_0\rangle, \quad (16)$$

where the $c(i)$ coefficients are equal to either $+1$ or -1 . How these signs distribute among the terms depend on the specific measurement outcome. The state described by the first summation in the above equation can be rewritten after the change of index $i \rightarrow \sigma$ as

$$|\Psi_1\rangle = \sum_{\sigma} c(\sigma) \left(\bigotimes_{i=1}^m |1\rangle_{i\sigma_i} \right) |+\rangle^{\otimes (m^2-m)}. \quad (17)$$

Although this is in general not the determinant state given in Eq. (13), Raz's technique can be modified

slightly to prove that the size of the associated multilinear formulas is still $m^{\Omega(\log m)}$, and hence this state is also super-polynomial in tree size. Since the quantum state $|\Psi_m\rangle$ is the sum of $|\Psi_1\rangle$ with tree-size $m^{\Omega(\log m)}$ and a product state with tree-size m^2 , it follows that the tree-size of this state must also be $m^{\Omega(\log m)}$ [35]. In short, we obtain a super-polynomial complex quantum state regardless of the measurement outcomes [36]. The quantum circuit for the $m = 2$ case is shown in Fig. (2).

Conclusion. – To conclude, we were able to construct explicitly a class of super-polynomial complex n -qubit quantum state when n is a square number. The tree size of these states, which we call the determinant and permanent states, has a lower bound of $n^{(1/4)\Omega(\log n)}$. The best upper bound we are able to find for the tree size is $O(\sqrt{n!})$ as given in Eq. (11). These states are highly symmetric due to the invariance of the determinant and permanent with respect to the interchange of any two rows or two columns. Finally, a quantum circuit for realizing a quantum state with super-polynomial tree size is proposed.




FIG. 2. A circuit with controlled-operations and ancilla qubits for creating the 4-qubit determinant state, or a state which is equivalently complex.

Acknowledgments. – We are grateful to A.J. Leggett, T. Lee and I. Arad for helpful comments and stimulating discussions. This work is supported by the Centre for Quantum Technologies (CQT). CQT is a Research Centre of Excellence funded by Ministry of Education and National Research Foundation of Singapore.

[1] S. Gröblacher, K. Hammerer, M.R. Vanner and M. Aspelmeyer, *Nature* **460**, 724 (2009).
[2] A.D. O'Connell, M. Hofheinz, M. Ansmann, R.C. Bialczak, M. Lenander, E. Lucero, M. Neeley, D. Sank, H. Wang, M. Weides, J. Wenner, J.M. Martinis, and A.N. Cleland, *Nature* **464**, 697 (2010).
[3] J. Friedman, V. Patel, W. Chen, S. Tolpygo and J. Lukens, *Nature* **46**, 43 (2000).
[4] L. Hackermüller, S. Uttenthaler, K. Hornberger, E. Reiger, B. Brezger, A. Zeilinger, and M. Arndt, *Phys. Rev. Lett.* **91**, 090408 (2003).
[5] T. Juffmann, A. Milic, M. Müllneritsch, P. Asenbaum A. Tsukernik, J. Tüxen, M. Mayor, O. Cheshnovsky, and M.

Arndt, *Nature Nanotechnology* **7**, 297 (2012).
[6] F. Fröwis and W. Dür, *New J. Phys.* **14**, 093039 (2012).
[7] A.J. Leggett, *Prog. Theor. Phys. Suppl.* **69**, 80 (1980).
[8] A. Shimizu and T. Miyadera, *Phys. Rev. Lett.* **89**, 270403 (2002).
[9] G. Björk G and P.G.L Mana, *J. Opt. B: Quantum Semi-class. Opt.* **6**, 429 (2004).
[10] J.I. Korsbakken, K.B. Whaley, J. Dubois and J.I. Cirac, *Phys. Rev. A* **75**, 042106 (2007).
[11] S. Nimmrichter, K. Hornberger, *Phys. Rev. Lett* **110**, 160403 (2013).
[12] G. Vidal, *Phys. Rev. Lett.* **91**, 147902 (2003).
[13] G. Vidal, *Phys. Rev. Lett.* **93**, 040502 (2004).

- [14] M.B. Hastings, J. Stat. Mech. P08024 (2007).
- [15] The vast majority of many-body quantum states in the Hilbert space can only be produced after an exponentially long time by local Hamiltonians [D. Poulin, A. Qarry, R. Somma, and F. Verstraete, Phys. Rev. Lett. **106**, 170501 (2011)], or have near-maximal entanglement [P. Hayden, D.W. Leung, and A. Winter, Comm. Math. Phys. **265**, 95 (2006); D. Gross, S.T. Flammia, and J. Eisert, Phys. Rev. Lett. **102**, 190501 (2009)].
- [16] S. Aaronson, STOC '04 Proceedings of the thirty-sixth annual ACM symposium on Theory of computing, pages 118-127 (2004); arXiv:quant-ph/0311039v4.
- [17] C.E. Mora and H.J. Briegel, Phys. Rev. Lett. **95**, 200503 (2005).
- [18] C. E. Mora, H. J. Briegel and B. Kraus, Int. J. Quantum Inform. **5**, 729 (2007).
- [19] F. Benatti, Nat. Comput. **6**, 133 (2006).
- [20] C. Rogers, V. Vedral and R. Nagarajan, Int. J. Quantum Inform. **6**, 907 (2008).
- [21] Y.C. Campbell-Borges and J.R.C. Piqueira, Int. J. Quant. Inf. **10**, 1250047 (2012).
- [22] R. Raz, Proc. ACM STOC, 633 (2004).
- [23] After a local projective measurement on a qubit, all the different states at the leaves corresponding to this qubit in the minimal tree are transformed to a single state and hence can be factorized out. It is clear that this operation can only reduce the tree size.
- [24] In Ref. [22] the size of a binary tree is defined as the number of nodes N which is related to the number of leaves L by $N = 2L - 1$. We neglect this difference by a factor of 2 in our work.
- [25] A. Acín, A. Andrianov, L. Costa, E. Jané, J.I. Latorre, and R. Tarrach, Phys. Rev. Lett. **85**, 1560 (2000).
- [26] For instance, take the state $\frac{1}{\sqrt{2}}(|00\rangle - |11\rangle)$: the direct recipe gives the multi-linear formula $\frac{1}{\sqrt{2}}[(1-x_1)(1-x_2) - x_1x_2]$, which has size 4; but this can be further expanded to $\frac{1}{\sqrt{2}}(1-x_1-x_2)$, which has size 2.
- [27] J. Williamson, Amer. Math. Monthly **52**, 417 (1945).
- [28] M. Živković, Linear Algebra and its Applications **414**, 310 (2006).
- [29] J. Brenner, Amer. Math. Monthly **79**, 626 (1972).
- [30] N. Metropolis and P.R. Stein, J. Combin Th. **3**, 191 (1967).
- [31] C.D. Meyer, *Matrix Analysis and Applied Linear Algebra* (SIAM, 2001), p. 549.
- [32] J. Eisert and H.J. Briegel, Phys. Rev. A **64**, 022306 (2001).
- [33] H.J. Briegel and R. Raussendorf, Phys. Rev. Lett. **86**, 910 (2001).
- [34] M. Hein, J. Eisert, and H.J. Briegel, Phys. Rev. A. **69**, 062311 (2004).
- [35] If $\text{TS}(\Psi_m) \leq m^{\epsilon \log m}$ for some positive constant ϵ then $\text{TS}(\Psi_1) \leq m^{\epsilon \log m} + m^2$. Thus, for any constant $\mu > \epsilon$ we have $\text{TS}(\Psi_1) < m^{\mu \log m}$ for sufficiently large m , which is a contradiction.
- [36] A circuit that prepares such a state is *not* a circuit that allows us to read the value of the multi-linear formula. In order to read the value of the formula from the corresponding state, one needs to estimate a probability that is exponentially small in the size of the matrix. In other words, it may be possible to find a simple circuit that produces those states, without any relation with the complexity of computing the formula. This is the same situation as in “boson sampling” where the output states have coefficients which are proportional to the permanent of matrices [M.A. Broome *et. al.*, Science **339**, 794 (2012); S. Aaronson and A. Arkhipov, 43rd annual Proc. ACM Symposium on Theory of Computing, 333 (2011)].